



General Description

The ZM027N03M combines advanced trench MOSFET technology with a low resistance package to provide extremely low $R_{DS(ON)}$. This device is ideal for switch and battery protection applications.


Features

- Advance high cell density Trench technology
- Low $R_{DS(ON)}$ to minimize conductive loss
- Low Gate Charge for fast switching
- Low Thermal resistance

Application

- MB/VGA Vcore
- SMPS 2nd Synchronous Rectifier
- POL application
- BLDC Motor driver


Product Summary



$V_{DS} = 30V$

$R_{DS(ON)} = 2.9m\Omega$

$I_D = 65A$



DFN3 x 3

Ordering Information:

Part NO.	ZM027N03M
Marking	027N03
Packing Information	REEL TAPE
Basic ordering unit (pcs)	5000

Absolute Maximum Ratings ($T_C = 25^\circ C$)

Parameter	Symbol	Rating	Unit
Drain-Source Voltage	V_{DS}	30	V
Gate-Source Voltage	V_{GS}	± 20	V
Continuous Drain Current	$I_{D@T_C=25^\circ C}$	65	A
	$I_{D@T_C=75^\circ C}$	49	A
	$I_{D@T_C=100^\circ C}$	40	A
	$I_{D@T_A=25^\circ C}$	21	A
	$I_{D@T_A=70^\circ C}$	17	A
Pulsed Drain Current ^①	I_{DM}	195	A
Total Power Dissipation	$P_{D@T_C=25^\circ C}$	46	W
Total Power Dissipation	$P_{D@T_A=25^\circ C}$	2.3	W
Operating Junction Temperature	T_J	-55 to 150	$^\circ C$
Storage Temperature	T_{STG}	-55 to 150	$^\circ C$



Single Pulse Avalanche Energy (L=0.1mH,VGS=10V,Rg=25Ω,TJ=25°C)	E_{AS}	180	mJ
---	----------	-----	----

•Thermal resistance

Parameter	Symbol	Min.	Typ.	Max.	Unit
Thermal resistance, junction - case	R_{thJC}	-	-	2.7	° C/W
Thermal resistance, junction - ambient	R_{thJA}	-	-	53	° C/W
Soldering temperature, wave soldering for 10s	T_{sold}	-	-	265	° C

•Electronic Characteristics

Parameter	Symbol	Condition	Min.	Typ	Max.	Unit
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{GS} = 0V, I_D = 250\mu A$	30			V
Gate Threshold Voltage	$V_{GS(TH)}$	$V_{GS} = V_{DS}, I_D = 250\mu A$	1.2		2.5	V
Drain-Source Leakage Current	I_{DSS}	$V_{DS} = 30V, V_{GS} = 0V$			1.0	μA
Gate- Source Leakage Current	I_{GSS}	$V_{GS} = \pm 20V, V_{DS} = 0V$			± 100	nA
Static Drain-source On Resistance	$R_{DS(ON)}$	$V_{GS} = 10V, I_D = 24A$		2.9	3.8	m Ω
		$V_{GS} = 4.5V, I_D = 12A$		4.6	5.5	m Ω
Forward Transconductance	g_{FS}	$V_{DS} = 25V, I_D = 10A$		30		s
Source-drain voltage	V_{SD}	$I_S = 24A$			1.28	V

•Dynamic Characteristics

Parameter	Symbol	Condition	Min.	Typ	Max.	Unit
Input capacitance	C_{iss}	$f = 1MHz,$ $V_{DS} = 25V$	-	2800	-	pF
Output capacitance	C_{oss}		-	420	-	
Reverse transfer capacitance	C_{rss}		-	280	-	
Gate Resistance	R_g	$f = 1MHz$		2.5		Ω
Total gate charge	Q_g	$V_{DD} = 25V$ $I_D = 8A$ $V_{GS} = 10V$	-	52	-	nC
Gate - Source charge	Q_{gs}		-	8.6	-	
Gate - Drain charge	Q_{gd}		-	13.8	-	
Turn-ON Delay time	$t_{D(on)}$	$V_{GS} = 10V, V_{DS} = 15V$		12		ns
Turn-ON Rise time	t_r			44		ns
Turn-Off Delay time	$t_{D(off)}$			50		ns



Turn-Off Fall time	t_f	$R_G = 3.3\Omega, I_D = 15A$		15		ns
Reverse Recovery Time	t_{RR}	$V_{DD} = 20V, dI_S/dt = 100A/\mu s, I_S = 30A$		5.8		ns
Charge Time	t_a			3.4		ns
Discharge Time	t_b			2.4		ns
Reverse Recovery Charge	Q_{RR}			1.6		nC

Note: ① Pulse Test : Pulse width $\leq 300\mu s$, Duty cycle $\leq 2\%$;

Fig.1 Power Dissipation




Fig.2 Typical output Characteristics




Fig.3 Threshold Voltage V.S Junction Temperature




Fig.4 Resistance V.S Drain Current






Fig.5 On-Resistance VS Gate Source Voltage




Fig.6 On-Resistance V.S Junction Temperature




Fig.7 SOA Maximum Safe Operating Area




Fig.8 ID-Junction Temperature




Figure 9. Diode Forward Voltage vs. Current




Figure 10. Transfer Characteristics




Figure 11. Gate-to-Source and Drain-to-Source Voltage vs. Total Charge




Fig.12 Capacitance Variation




Fig.13 Switching Time Measurement Circuit




Fig.14 Gate Charge Waveform




Fig.15 Avalanche Measurement Circuit




Fig.16 Avalanche Waveform








Fig.17 Gate Charge Waveform






•Dimensions(DFN3×3)

Unit: mm



L O B M S	DFN3.3x3.3-8			
	MILLIMETERS		INCHES	
	MIN.	MAX.	MIN.	MAX.
A	0.70	1.00	0.028	0.039
A1	0.00	0.05	0.000	0.002
b	0.25	0.35	0.010	0.014
c	0.14	0.20	0.006	0.008
D	3.10	3.50	0.122	0.138
D1	3.05	3.25	0.120	0.128
D2	2.35	2.55	0.093	0.100
E	3.10	3.50	0.122	0.138
E1	2.90	3.10	0.114	0.122
E2	1.64	1.84	0.065	0.072
e	0.65 BSC		0.026 BSC	
H	0.32	0.52	0.013	0.020
K	0.59	0.79	0.023	0.031
L	0.25	0.55	0.010	0.022

RECOMMENDED LAND PATTERN



UNIT: mm