



**• General Description**


The ZMC88601S combines advanced trench MOSFET technology with a low resistance package to provide extremely low  $R_{DS(ON)}$ . It combine one N Channel MOSFET and one P channel MOSFET.

**• Features**

- Advance high cell density Trench technology
- Low  $R_{DS(ON)}$  to minimize conductive loss
- Low Gate Charge for fast switching
- Dual DIE in one package

**• Product Summary**


$V_{DS1} = 60V$   
 $V_{DS2} = -60V$   
 $R_{DS(ON)1} = 43m\Omega$   
 $R_{DS(ON)2} = 57m\Omega$   
 $I_{D1} = 4.5A$   
 $I_{D2} = -4.0A$



SOP8

**• Application**

- Power Management in Notebook Computer
- BLDC Motor driver

**• Ordering Information:**

Part NO.	ZMC88601S
Marking	ZMC88601
Packing Information	REEL TAPE
Basic ordering unit (pcs)	4000

**• N Channel Absolute Maximum Ratings ( $T_c = 25^\circ C$ )**

Parameter	Symbol	Rating	Unit
Drain-Source Voltage	$V_{DS}$	60	V
Gate-Source Voltage	$V_{GS}$	$\pm 20$	V
Continuous Drain Current <sup>②</sup>	$I_D$	4.5	A
Pulsed Drain Current <sup>①</sup>	$I_{DM}$	13	A
Total Power Dissipation <sup>②</sup>	$P_D @ T_C = 25^\circ C$	3.4	W
Total Power Dissipation	$P_D @ T_A = 25^\circ C$	0.69	W
Operating Junction Temperature	$T_J$	-55 to 150	$^\circ C$
Storage Temperature	$T_{STG}$	-55 to 150	$^\circ C$


**•P Channel Absolute Maximum Ratings ( $T_c = 25^\circ\text{C}$ )**

Parameter	Symbol	Rating	Unit
Drain-Source Voltage	$V_{DS}$	-60	V
Gate-Source Voltage	$V_{GS}$	$\pm 20$	V
Continuous Drain Current( $T_C = 25^\circ\text{C}$ )	$I_D$	-4.0	A
Pulsed Drain Current <sup>①</sup>	$I_{DM}$	-12	A
Total Power Dissipation <sup>②</sup>	$P_D @ T_C = 25^\circ\text{C}$	3.6	W
Total Power Dissipation	$P_D @ T_A = 25^\circ\text{C}$	0.69	W
Operating Junction Temperature	$T_J$	-55 to 150	$^\circ\text{C}$
Storage Temperature	$T_{STG}$	-55 to 150	$^\circ\text{C}$

**•Thermal resistance**

Parameter	Symbol	Min.	Typ.	Max.	Unit
Thermal resistance, junction - case	$R_{thJC}$	-	-	56	$^\circ\text{C}/\text{W}$
Thermal resistance, junction - ambient	$R_{thJA}$	-	-	180	$^\circ\text{C}/\text{W}$
Soldering temperature, wavesoldering for 10s	$T_{sold}$	-	-	265	$^\circ\text{C}$

**•N Channel Electronic Characteristics**

Parameter	Symbol	Condition	Min.	Typ	Max.	Unit
Drain-Source Breakdown Voltage	$BV_{DSS}$	$V_{GS} = 0\text{V}, I_D = 250\mu\text{A}$	60			V
Gate Threshold Voltage	$V_{GS(TH)}$	$V_{GS} = V_{DS}, I_D = 250\mu\text{A}$	1.2		2.5	V
Drain-Source Leakage Current	$I_{DSS}$	$V_{DS}=60\text{V}, V_{GS} = 0\text{V}$			1.0	$\mu\text{A}$
Gate- Source Leakage Current	$I_{GSS}$	$V_{GS}=\pm 20\text{V}, V_{DS} = 0\text{V}$			$\pm 100$	nA
Static Drain-source On Resistance	$R_{DS(ON)}$	$V_{GS}=10\text{V}, I_D=4\text{A}$		43	50	$\text{m}\Omega$
		$V_{GS}=4.5\text{V}, I_D=3\text{A}$		75	85	$\text{m}\Omega$
Forward Transconductance	$g_{FS}$	$V_{DS} = 10\text{V}, I_D=4\text{A}$		10		s
Diode Forward Voltage	$V_{FSD}$	$I_{SD}=4\text{A}$			1.28	V

**•Electronic Characteristics**

Parameter	Symbol	Condition	Min.	Typ	Max.	Unit
Input capacitance	$C_{iss}$	$V_{DS}=25\text{V}$ $f = 1\text{MHz}$	-	1050	-	pF
Output capacitance	$C_{oss}$		-	255	-	
Reverse transfer capacitance	$C_{rss}$		-	185	-	


**•Gate Charge characteristics( $T_a = 25^\circ\text{C}$ )**

Parameter	Symbol	Condition	Min.	Typ	Max.	Unit
Total gate charge	Qg	VDD = 25V ID = 4A VGS = 10V	-	12	-	nC
Gate - Source charge	Qgs		-	5	-	
Gate - Drain charge	Qgd		-	4	-	

**•P Channel Electronic Characteristics**

Parameter	Symbol	Condition	Min.	Typ	Max.	Unit
Drain-Source Breakdown Voltage	$\text{BV}_{\text{DSS}}$	$V_{\text{GS}} = 0\text{V}, I_{\text{D}} = -250\mu\text{A}$	-60			V
Gate Threshold Voltage	$V_{\text{GS(TH)}}$	$V_{\text{GS}} = V_{\text{DS}}, I_{\text{D}} = -250\mu\text{A}$	-1.0		-2.5	V
Drain-Source Leakage Current	$I_{\text{DSS}}$	$V_{\text{DS}} = -60\text{V}, V_{\text{GS}} = 0\text{V}$			-1.0	$\mu\text{A}$
Gate- Source Leakage Current	$I_{\text{GSS}}$	$V_{\text{GS}} = \pm 20\text{V}, V_{\text{DS}} = 0\text{V}$			$\pm 100$	nA
Static Drain-source On Resistance	$R_{\text{DS(ON)}}$	$V_{\text{GS}} = -10\text{V}, I_{\text{D}} = -4\text{A}$		57	74	$\text{m}\Omega$
		$V_{\text{GS}} = -4.5\text{V}, I_{\text{D}} = -3\text{A}$		76	100	$\text{m}\Omega$
Forward Transconductance	$g_{\text{FS}}$	$V_{\text{DS}} = -10\text{V}, I_{\text{D}} = -3\text{A}$		9		s
Diode Forward Voltage	$V_{\text{FSD}}$	$I_{\text{SD}} = -4\text{A}$			-1.28	V

**•Electronic Characteristics**

Parameter	Symbol	Condition	Min.	Typ	Max.	Unit
Input capacitance	$C_{\text{iss}}$	$V_{\text{DS}} = 25\text{V}$ $f = 1\text{MHz}$	-	1550	-	pF
Output capacitance	$C_{\text{oss}}$		-	160	-	
Reverse transfer capacitance	$C_{\text{rss}}$		-	140	-	

**•Gate Charge characteristics( $T_a = 25^\circ\text{C}$ )**

Parameter	Symbol	Condition	Min.	Typ	Max.	Unit
Total gate charge	Qg	$V_{\text{DD}} = -25\text{V}$ $ID = -4\text{A}$ $V_{\text{GS}} = -10\text{V}$	-	23	-	nC
Gate - Source charge	Qgs		-	4	-	
Gate - Drain charge	Qgd		-	9	-	

**•N Channel characteristics curve**

Fig.1 Power Dissipation Derating Curve




Fig.2 Typical output Characteristics




Fig.3 Threshold Voltage V.S Junction Temperature




Fig.4 Resistance V.S Drain Current




Fig.5 On-Resistance VS Gate Source Voltage





Fig.6 On-Resistance V.S Junction Temperature



**•P Channel characteristics curve**

Fig.1 Power Dissipation Derating Curve




Fig.2 Typical output Characteristics




Fig.3 Threshold Voltage V.S Junction Temperature




Fig.4 Resistance V.S Drain Current




Fig.5 On-Resistance VS Gate Source Voltage





Fig.6 On-Resistance V.S Junction Temperature



•Test Circuit

Fig.1 Gate Charge Measurement Circuit




Fig.2 Gate Charge Waveform




Fig.3 Switching Time Measurement Circuit




Fig.4 Switching Time Waveform




Fig.5 Avalanche Measurement Circuit





Fig.6 Avalanche Waveform





## •Dimensions(SOP8)

Unit: mm

SYMBOL	min	TYP	max	SYMBOL	min		max
A	4.80		5.00	C	1.30		1.50
A1	0.37		0.47	C1	0.55		0.75
A2		1.27		C2	0.55		0.65
A3		0.41		C3	0.05		0.20
B	5.80		6.20	C4	0.19	0.20	0.23
B1	3.80		4.00	D		1.05	
B2		5.00		D1	0.40		0.62

